

MV-CH123-10GM/GC

12.3 MP CMOS GigE Area Scan Camera


GEN*<i>i>*CAM
GiG*E*
VISION

Introduction

MV-CH123-10GM/GC camera adopts Sony® IMX545 sensor to provide high-quality images. It uses GigE interface to transmit non-compressed images in real time, and its max. frame rate can reach 9.5 fps in full resolution.

Key Features

- Adopts compact design with mounting holes on panels for flexible mounting from 4 sides, and supports C-mount lens.
- Supports auto or manual adjustment of gain and exposure time, and manual adjustment of LUT and Gamma correction.
- Supports LSC, Sequencer, passive transmission, etc.
- Color camera supports white balance, CCM, Super Palette, Super Bayer, etc.
- Compatible with GigE Vision Protocol V2.0, GenICam Standard, and third-party software based on these protocol and standard.


Available Model

- Mono camera: MV-CH123-10GM
- Color camera: MV-CH123-10GC


Applicable Industry

Electronic semiconductor, factory automation, logistics code reading, medicine packing, etc.

Sensor Quantum Efficiency




MV-CH123-10GM



MV-CH123-10GC

Dimension



Unit: mm

Specification

Model	MV-CH123-10GM	MV-CH123-10GC
Performance		
Sensor type	CMOS, global shutter	
Sensor model	Sony® IMX545	
Pixel size	2.74 μm × 2.74 μm	
Sensor size	1/1.1"	
Resolution	4096 × 3000	
Max. frame rate	9.5 fps @ 4096 × 3000 Mono 8	9.5 fps @ 4096 × 3000 Bayer RG 8
Dynamic range	69.4 dB	69.2 dB
SNR	39.2 dB	39.1 dB
Gain	0 dB to 24 dB	
Exposure time	UltraShort exposure mode: 1 μs to 2 μs Standard exposure mode: 3 μs to 10 sec	
Exposure mode	Off/Once/Continuous exposure mode	
Mono/color	Mono	Color
Pixel format	Mono 8/10/10Packed/12/12Packed	Mono 8/10/12, Bayer RG 8/10/10Packed/12/12Packed, YUV422Packed, YUV422_YUYV_Packed, RGB 8, BGR 8
Binning	Supports 1 × 1, 2 × 2, 4 × 4	
Decimation	Supports 1 × 1, 2 × 2, 4 × 4	
Reverse image	Supports horizontal and vertical reverse image output	
Electrical feature		
Data interface	Gigabit Ethernet (1000 Mbit/s), compatible with Fast Ethernet (100 Mbit/s)	
Digital I/O	6-pin P7 connector provides power and I/O, including opto-isolated input × 1 (Line 0), opto-isolated output × 1 (Line 1), bi-directional non-isolated I/O × 1 (Line 2).	
Power supply	9 VDC to 24 VDC, supports PoE	
Power consumption	Typ. 2.4 W @ 12 VDC	Typ. 2.5 W @ 12 VDC
Mechanical		
Lens mount	C-mount	
Dimension	29 mm × 29 mm × 42 mm (1.1" × 1.1" × 1.7")	
Weight	101.6 g (0.2 lb.)	
Ingress protection	IP40 (under proper lens installation and wiring)	
Temperature	Working temperature: −10 °C to 50 °C (14 °F to 122 °F) Storage temperature: −30 °C to 80 °C (−22 °F to 176 °F)	
Humidity	20% RH to 95% RH (no condensation)	
General		
Client software	MVS or third-party software meeting with GigE Vision Protocol	
Operating system	32/64-bit Windows 7/10, 64-bit Windows 11, and 32/64-bit Linux	
Compatibility	GigE Vision V2.0, GenICam	
Certification	CE, RoHS, KC	